



Ultra Phantom Omnidirectional Antenna

Laird's unique patented Ultra Phantom® single-band antenna is a rugged low-profile antenna for outdoor or indoor applications. The Ultra Phantom features vertical polarization, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Laird magnetic, trunk lid and whole mounts.

FEATURES AND BENEFITS

- Outperforms 3-dBi whip antennas in many applications
- IP67-rated for harsh environment applications
- U.S. patent numbers 5,977,931 - 6,292,156 and 7,209,096
- RoHS-compliant

APPLICATIONS

- Public safety
- Transportation
- Utilities
- Military mobile
- Fixed radio applications

ELECTRICAL SPECIFICATIONS

Frequency Range	380-512 (see Model and Ordering Information)
VSWR - Avg	≤ 2.5:1
Gain (dBi)	2.0 - 4.1 (see Model and Ordering Information)
Max Power - Ambient 25°C (W)	100
Nominal Impedance (Ohms)	50
Pattern Type	Omnidirectional
Polarization	Vertical

MECHANICAL SPECIFICATIONS

Dimensions - diameter x height - mm (inches)	35.5 x 86.3 (1.4 x 3.4)
Weight - g (lbs.)	163.3 (0.36)
Mounting	NMO
Color	Black or white
Lightning Protection	

ENVIRONMENTAL SPECIFICATIONS


Operating Temperature - °C (°F)	-45 to +85°C (-49 to +185°F)
Storage Temperature - °C (°F)	-50 to +85°C (-58 to +185°F)
Wind Survival - km/hr (mph)	282 (175)
Ingress Protection Rating	IP67
Material Substance Compliance	RoHS

MODEL AND ORDERING INFORMATION


PART NUMBER	FREQUENCY (MHZ)	MAX. GAIN (DBI)	COLOR
UTRA4502S3NB-001/ UTRA4502S3NW-001	450-512	4.1	Black/White
UTRA4301S3NB-001/ UTRA4301S3NW-001	430-490	3.6	Black/White
UTRA4061S2NB-001/ UTRA4061S2NW-001	406-440	2.9	Black/White
UTRA3802S1NB-001/ UTRA3802S1NW-001	380-410	2.0	Black/White

RADIATION PATTERNS


450 MHz




430 MHz




406 MHz




380 MHz




512 MHz




490 MHz



440 MHz



410 MHz



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original

