

Gen-Lock Reference SYNC Generator **TGEN-6P**

Professional 3G-SDI Gen-lock Generator

The TGEN-6P generates 3G-SDI and HD-SDI Gen-lock Sync reference, while giving you the ability to sync all your video sources into one master sync signal. It supports 15 different formats ranging from 720p 25Hz up to 1080p 59.94/60Hz and can be operated in Slave mode, distributing external reference sync signals. TGEN-6P has a built-in LCD screen and dip-switches for convenient setting and status checking. Its compact and solid design helps users create and maintain a more streamlined workflow.



KEY FEATURES:

- HD TRI-LEVEL OUT
- 1080p**
59.94Hz
- PROGRESSIVE
INTELACED
- SMPTE**
274M/296M
- CASCADING
Bi Level Tri-Level

APPLICATIONS:



LIVE PRODUCTION



WORSHIP



VIDEO CONFERENCE



MEDICAL



THEATER

MAIN FEATURES


- Multi format HD Tri Level Sync up to 1080p60.
- Both V Sync and H Sync generation for more accurate timing.
- Up to 6 synchronized reference output per device.
- Slave mode for cascading.
- Built in LCD screen.
- Built in setting dip-switches.
- Versatile, compact, and rugged design

SPECIFICATIONS

VIDEO		STANDARD	
Reference Out	Tri-Level HD	SMPTE	SMPTE 274M, SMPTE 296M
Format	1080p 60/59.94/50/30/29.97/25Hz 1080i 60/59.94/50Hz 720p 60/59.94/50/30/25Hz	PHYSICAL	
Accuracy	2ppm	Control	Dip-switches & Text LCD
Reference In	Tri-Level HD & Bi-Level SD	Operation Temp	32°F - 104°F
		Dimension	129mm x 86mm x 29mm / 5.07" x 3.38" x 1.10"
		Weight	278g / 0.61lbs
		Power	12VDC (+9 - +15VDC)

**Specification are subject to change without notice.*

PACKAGE CONTENTS



DC 12v Power Supply & Sockets Adapter